

Negotiated Re-Roof Projects and New Roof Project Request

Your quote request needs to include the following project information:

- 1) Job Name, Job Location (City, State), contractor's name, contractor's contact information, ABC branch location and branch contact information.
- 2) Job request must have bid date and/or date needed.
- 3) What type of tapered insulation material is being requested (ISO - *Polyisocyanurate*, EPS - *Expanded Polystyrene*, XPS - *Extruded Polystyrene*, Perlite - *Fesco*)
- 4) The direction of slope and desired pitch of the tapered system (1/16", 1/8", 1/4", 3/8", 1/2") "*Tapered System includes tapered panels and fill insulation only required to achieve slope*" (**not base layer**)
- 5) The desired pitch of the cricket or saddle system "*Typically twice the slope of the field*" (1/4", 1/2", 3/4", 1", etc.)
- 6) The existing deck slope is required when requesting cricket or saddle only estimates to design crickets correctly.
- 7) The minimum starting thickness of the tapered system only, excluding any materials to be installed under the tapered system (*i.e. base layer*) or over the tapered system (*i.e. overlay*)
- 8) If there is a maximum overall thickness required for the tapered system to maintain a specified height at any parapet wall, wood blocking, drip edge, or any abnormal situations.
- 9) When you send architecturally drawn roof plans to us, they must be full size and to scale or have dimensions on the plans and list specific pages for roof plans, sections, details, etc to facilitate your quote.
- 10) Any EagleView, Roof R Roof Report, or Similar types roof reports **must** show the roof's entire perimeter dimensions and clearly locate all drains with dimensions, gutters, scuppers, skylights, roof top units, interior roof areas, etc.
- 11) Any hand sketched roof plans must show the roof's entire perimeter dimensions and clearly locate all drains, gutters, scuppers, skylights, roof top units, interior roof areas, etc.
- 12) The required R-value if specified and if the requirement pertains to a minimum R-value (*i.e. lowest point anywhere on the roof area*) or average R-value (*i.e. overall average thickness of the roof area*)

NOTE: All of the information listed above must be listed on the "**Tapered Request Form**" to receive a taper quote



Request for Tapered Quote

tapered@abcsupply.com

Bill Rosado – Northeast and Southeast: bill.rosado@abcsupply.com

David Haley – Midwest, Southwest, and West: david.haley@abcsupply.com

Today's Date: _____ Bid Date: _____ (or) Date Needed: _____

Job Name: _____

City: _____ State: _____

Company Name: _____

Contact Name: _____

Phone Number: _____ Email: _____

ABC Supply Sales Person: _____

ABC Supply Branch City & State: _____

Roof Drawings:

Attached Via: Email Online (specify below) Other Source: _____

List page number of roof plans, sections, details, etc. _____

Project Specifications (must be completed):

Tapered Material: ISO PSI Perlite EPS (Density) XPS (Type) _____

Taper Slope: 1/8" 1/4" 3/8" 1/2" Other _____

Cricket Slope: 1/4" 1/2" 3/4" 1" Other _____

Minimum Thickness: _____ Maximum Thickness: _____

R-Value: Minimum _____ Average _____

Base Layer: ISO Perlite EPS _____ Thickness Other: _____

Notes: